

| Product | Colour | Viscosity at 40 °C [mm²/s] | Anwendung | Leistung |
|-----------|-----------------------|-------------------------------|-----------------------------------|-----------|
| CLF 90 | bernsteinfarben | 90 | Edelstahl, Stahl, Alu, Buntmetall | ● ● ● |
| CLF 100 | bernsteinfarben | 100 | Edelstahl, Stahl, Alu, Buntmetall | ● ● ● ● |
| KTL N 16 | bernsteinfarben | 160 | Stahl, Alu, Buntmetall | ● ● ● |
| CLF 180 | bernsteinfarben | 180 | Edelstahl, Stahl, Alu, Buntmetall | ● ● ● ● ● |
| CLF 180 S | bernsteinfarben | 180 | Edelstahl, Stahl, Alu | ● ● ● ● ● |
| CLF W 100 | bernsteinfarben, opac | 100 | Stahl, Alu, Buntmetall | ● ● |
| CLF W 430 | bernsteinfarben, opac | 430 | Stahl, Alu, Buntmetall | ● ● ● |
| CLF 100 V | bernsteinfarben | 100 | Stahl, Alu, Buntmetall | ● ● ● ● |

Performance overview

Low < <

> > High



CLF W 100

CLF 90
CLF W 430

CLF 100

KTL N 16
CLF 180
CLF 180 S

The above mentioned information on the area of application are based on lab tests and practical experiences. These instructions do not release the user from checking the suitability of the lubricant and its application and follow-up processes.
We reserve the rights to make changes due to new laws, regulations, perceptions, etc.